

ROTARY COMPRESSORS | AIR TREATMENT

Total Solution Provider



Gardner Denver

provides the broadest range of air compressors that handle a wide-variety of applications. From the most demanding, requiring compressed air 24/7/365 to the fluctuating day-to-day or shift-to-shift, we have the right compressor to maximize productivity and energy savings.



FIXED SPEED | OIL-FLOODED ROTARY COMPRESSORS



hydrovane

Versatile

- 2-60 HP
- 100-150 PSIG
- 5-227 CFM



L Series

Simplistic

- 5-400 HP
- 75-190 PSIG
- 13-1604 CFM



Electra-Saver II/G2

Slow Speed Reliability

- 40-200 HP
- 100-200 PSIG
- 137-1091 CFM



Electra-Saver/G2

Turn-Valve Efficiency

- 75-500 HP
- 100-150 PSIG
- 342-2459 CFM

VARIABLE SPEED | OIL-FLOODED ROTARY COMPRESSORS



hydrovane

Investment Effective

- 7-45 kW
- 100-150 PSIG
- 47-264 CFM



LRS Series

Energy Efficiency

- 7-290 kW
- 75-190 PSIG
- 29-1620 CFM



VST Series

Ultimate Efficiency

- 55-260 kW
- 100-175 PSIG
- 336-2032 CFM

OIL-FREE | COMPRESSORS















EnviroAire S & ES EnviroAire VS

- 3-10 HP
- 116-140 PSIG
- 8-126 CFM

- 15-110 kW
- 75-145 PSIG
- 65-655 CFM

EnviroAire T

- 75-315 kW
- 115-145 PSIG
- 383-1705 CFM

EnviroAire TVS

- 110-315 kW
- 115-145 PSIG
- 316-1596 CFM

Ultima

- 75-160 kW
- **247-842 CFM**
- 75-145 PSIG

Quantima

- 150-300 kW
- 750-1860 CFM
- 73-116 PSIG

REFRIGERATED DRYERS

RPC Series

Energy Saving

- 75-2,000 CFM
- Latest Advancement in Heat Transfer Technology

RNC Series

Non-Cycling

- 10-150; 750-3,000 CFM
- Integrated Grade B Filter
- Cold Coalescing Filter Option

RGD Series

Non-Cycling

- 2.5-500 CFM
- Air-Cooled
- 2-Year Warranty

GSRN Series

Non-Cycling

- 10-2,250 CFM
- Air-Cooled and Water-Cooled
- Stainless Steel Components

GTRC Series

Cycling Dryer

- 100-2,250 CFM
- Adjustable Dewpoint
- Stainless Steel Components

RHT/GHRN Series

High Temp

- 20-132 CFM
- Up to 180°F Inlet Temperature

RHP

High Pressure

- 30-3,000 CFM
- Up to 725 PSIG Inlet Pressure

DESICCANT DRYERS

DGH Series

Heatless

- 3-5.400 CFM
- Dewpoint to -100°F

DHP/GEHD Series

Externally Heated

- 100-4.000 CFM
- Dewpoint to -40°F

DPB/GBPD Series

Blower Purge

- 100-4.300 CFM
- Dewpoint to -40°F

DHC Series

Heat of Compression

- 350-10.000 CFM
- Dewpoint Demand Control

MEMBRANE DRYERS, NITROGEN GENERATORS, CHILLERS, FILTERS, PIPING, LUBRICANTS, & CONDENSATE MANAGEMENT

Membrane Dryers

MES/MMD Series

- 1.5-138 CFM
- Dewpoint to -40°F

Nitrogen Generators

GDN2 Series

- 98-99.999% Purity
- Skid-Mounted PSA Design

Process Chillers

CHL Series

- 0.6-104.6 Tons
- Integral Pump and Manual Bypass

Filters

FIL/GIL Series

- 20-21,250 CFM
- High Pressure and High Temperature Filters Available

Piping

Quick-Lock & Big Lock Series

- Sizes from 0.5-10"
- Extruded Aluminum Piping
- All Metal Fittings

Lubricants

AEON Lubricant

- 8,000 Hr Synthetic Blends
- Food Grade Available
- High Temperature Blends

Mist Eliminators

FME Series

- 125-3,000 CFM

Oil/Water Separators

GD PAK/CTS/CTS-T Series

 Effectively Treats Contaminated Condensate

Intelli-PAK

- Cabinet PAK Design
- Proprietary Tank Connections

Drains

SMD/DS/EDDS Series

- Zero-Loss
- Electric Timed Drain



The leader in every market we serve by continuously improving all business processes with a focus on innovation and velocity



Gardner Denver, Inc.

1800 Gardner Expressway Quincy, IL 62305 866-440-6241 www.gardnerdenver.com/gdproducts









©2020 Gardner Denver, Inc. Printed in U.S.A. GS-LINE 11th Ed. 8/20

